



SPECIFICATIONS

Advanta AW-03

Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
215/55R17 98V XL	Pending	lbs			28 lbs							TH
225/45R17 94V XL	600 A A	1,477 lbs	50 psi		24 lbs				7.5"			TH
225/50R17 98V XL	Pending	lbs			28 lbs							TH
225/55R17 101V XL	600 A A	1,819 lbs	50 psi		28 lbs				7.3"			TH
225/60R17 99V SL	600 A A	1,709 lbs	44 psi		28 lbs				6.8"			TH
225/65R17 102H SL	600 A A	1,874 lbs	44 psi		30 lbs				6.7"			TH
235/55R17 103V XL	Pending	lbs			25 lbs							TH
235/65R17 108V XL	600 A A	2,205 lbs	50 psi		30 lbs				7.3"			TH
225/55R18 98V SL	600 A A	1,653 lbs	44 psi		28 lbs				7.2"			TH
225/60R18 104H XL	600 A A	1,984 lbs	50 psi		28 lbs				6.6"			TH
235/45R18 98V XL	Pending	lbs			27 lbs							TH
235/55R18 100V SL	600 A A	1,764 lbs	44 psi		29 lbs				7.5"			TH
235/60R18 107V XL	600 A A	2,149 lbs	50 psi		31 lbs				7.3"			TH
235/65R18 106H SL	600 A A	2,094 lbs	44 psi		32 lbs				7.3"			TH
245/45R18 100V XL	600 A A	1,764 lbs	50 psi		27 lbs				8.3"			TH
245/60R18 105V SL	600 A A	2,039 lbs	44 psi		32 lbs				7.5"			TH
255/60R18 112V XL	600 A A	2,469 lbs	50 psi		34 lbs				7.9"			TH
225/55R19 103V XL	600 A A	1,929 lbs	50 psi		29 lbs				7.4"			TH
235/40R19 96V XL	Pending	lbs			23 lbs							TH
235/55R19 105V XL	600 A A	2,039 lbs	50 psi		31 lbs				7.7"			TH
235/55R20 102V SL	600 A A	1,874 lbs	44 psi		32 lbs				7.6"			TH
245/50R20 105V XL	600 A A	2,039 lbs	50 psi		31 lbs				7.8"			TH
255/50R20 109V XL	600 A A	2,271 lbs	51 psi		34 lbs				8.2"			TH
255/55R20 110V XL	600 A A	2,337 lbs	50 psi		36 lbs				8.1"			TH



Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
275/55R20 117H XL	Pending	lbs			42 lbs							TH
285/45R22 114H XL	600 AA	2,601 lbs	50 psi		38 lbs				9.1"			TH

NOTES

Specifications shown are as accurate as possible based on the information provided to us by the tire manufacturers. The dimensions reflect average values for tires measured on the specified measuring rim width. Individual tires may vary from data shown.

All tires are subject to continuous development. The tire manufacturers and Tire Rack reserve the right to change product specifications at any time without notice or obligation.

*Although regularly updated, the country of origin for tires may vary from what is shown. Unfortunately, we cannot accommodate requests for tires with a specific country of origin.

For assistance selecting products for your vehicle, please contact our sales specialists at 888-541-1777 or via email