



SPECIFICATIONS

Firestone Destination LE4

Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
215/70R16 100H SL	700 A B	1,764 lbs	51 psi	11/32"	24 lbs	5.5-7"	6.5"	8.7"	5.5"	27.9"	747	MX
235/75R16 108T SL	700 A B	2,205 lbs	51 psi	12/32"	31 lbs	6-8"	7"	9.3"	8.6"	29.8"	698	MX
245/75R16 111T SL	Pending	2,403 lbs	51 psi	12/32"	30 lbs	6.5-8"	7"	9.8"		30.5"	684	MX
215/60R17 96H SL	Pending	1,565 lbs	51 psi	11/32"	26 lbs	6-7.5"	6.5"	8.7"		27.2"	766	MX
215/65R17 99H SL	700 A B	1,709 lbs	51 psi	11/32"	24 lbs	6-7.5"	6.5"	8.7"	5.7"	28"	743	MX
235/70R17 109T XL	700 A B	2,271 lbs	50 psi	12/32"	31 lbs	6-8"	7"	9.5"	5.8"	30"	694	MX
255/70R17 112T SL	700 A B	2,469 lbs	51 psi	12/32"	37 lbs	6.5-8.5"	8"	10.2"	7.3"	31.1"	670	CA
265/70R17 115T SL	700 A B	2,679 lbs	51 psi	12/32"	37 lbs	7-9"	8"	10.7"	7.5"	31.7"	658	CA
255/50R20 109V XL	Pending	2,271 lbs	50 psi	11/32"	35 lbs	7-9"	8"	10.4"		30.1"	693	MX
255/55R20 107H SL	Pending	2,149 lbs	51 psi	12/32"	26 lbs	7-9"	8"	10.4"		31"	672	MX

NOTES

Specifications shown are as accurate as possible based on the information provided to us by the tire manufacturers. The dimensions reflect average values for tires measured on the specified measuring rim width. Individual tires may vary from data shown.

All tires are subject to continuous development. The tire manufacturers and Tire Rack reserve the right to change product specifications at any time without notice or obligation.

*Although regularly updated, the country of origin for tires may vary from what is shown. Unfortunately, we cannot accommodate requests for tires with a specific country of origin.

For assistance selecting products for your vehicle, please contact our sales specialists at 888-541-1777 or via email