



## SPECIFICATIONS

### Kenda Spare Tire K801

Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
T135/80D15 99M SL	None	1,709 lbs	60 psi		10 lbs	3.5-4.5"	3.5"		3.1"			CN
T135/80D15 99M SL	None	1,709 lbs	60 psi		10 lbs	3.5-4.5"	3.5"		3.6"			CN
T125/80D16 97M SL	None	1,609 lbs	60 psi	3/32"	9 lbs	3-4"	3.5"		4"			TW
T125/85D16 99M SL	None	1,708 lbs	60 psi	3/32"	9 lbs	3-4"	3.5"		3.5"			TW
T135/80D16 101M SL	None	1,819 lbs	60 psi	4/32"	12 lbs	3.5-4.5"	3.5"		4"			TW
T135/90D16 102M SL	None	1,874 lbs	60 psi		11 lbs	3.5-4.5"	3.5"		3.9"			CN
T125/70R17 98M SL	None	1,653 lbs	60 psi		10 lbs	3-4"	3.5"		3.7"			CN
T135/80D17 103M SL	None	1,929 lbs	60 psi		11 lbs	3.5-4.5"	3.5"		3.8"			CN
T135/90D17 104M SL	None	1,984 lbs	60 psi		11 lbs	3.5-4.5"	3.5"		3.8"			CN
T155/90D17 101M SL	None	1,819 lbs	60 psi		17 lbs	4-5"	4.5"		3.9"			TW, CN
T155/90D17 112M SL	None	2,469 lbs	60 psi		17 lbs	4-5"	4.5"		3.9"			CN, TW
T155/80R19 114M SL	None	2,601 lbs	50 psi		18 lbs	4-5"	4.5"		4"			TW
T145/60R20 105M SL	None	2,039 lbs	60 psi		13 lbs	4-5"	4.5"		4.4"			TW

## NOTES

Specifications shown are as accurate as possible based on the information provided to us by the tire manufacturers. The dimensions reflect average values for tires measured on the specified measuring rim width. Individual tires may vary from data shown.

All tires are subject to continuous development. The tire manufacturers and Tire Rack reserve the right to change product specifications at any time without notice or obligation.

\*Although regularly updated, the country of origin for tires may vary from what is shown. Unfortunately, we cannot accommodate requests for tires with a specific country of origin.

For assistance selecting products for your vehicle, please contact our sales specialists at 888-541-1777 or via email