



SPECIFICATIONS

Nokian Hakkapeliitta 01 (Studded)

Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
235/45R20 100T XL Double Action Stud SilentDrive	None	1,764 lbs	51 psi	11.5/32"	30 lbs	7.5-9"	8"	9.3"	7.6"	28.4"	731	FI
175/65R14 86T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	15 lbs	5-6"	5"	7"		23"	900	FI
175/65R15 88T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	16 lbs	5-6"	5"	7"		24"	869	FI
185/60R15 88T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	18 lbs	5-6.5"	5.5"	7.4"		23.7"	876	FI
185/65R15 92T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	17 lbs	5-6.5"	5.5"	7.4"		24.5"	847	FI
195/65R15 95T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	18 lbs	5.5-7"	6"	7.9"		25"	834	FI
195/55R16 91T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	19 lbs	5.5-7"	6"	7.9"		24.4"	855	FI
205/55R16 94T XL Double Action Stud Technology	None	1,477 lbs	51 psi	11.5/32"	22 lbs	5.5-7.5"	6.5"	8.4"	6.7"	24.9"	834	FI
205/60R16 96T XL Double Action Stud Technology	None	1,565 lbs	51 psi	11.5/32"	21 lbs	5.5-7.5"	6"	8.2"		25.7"	807	FI
205/65R16 99T XL Double Action Stud Technology	None	1,710 lbs	51 psi	11.5/32"	22 lbs	5.5-7.5"	6"	8.2"		26.5"	781	FI
215/60R16 99T XL Double Action Stud Technology	None	1,710 lbs	51 psi	11.5/32"	25 lbs	6-7.5"	6.5"	8.7"		26.1"	794	FI
215/65R16 102T XL	None	1,874 lbs	51 psi	11.5/32"	26 lbs	6-7.5"	6.5"	8.7"	6.9"	27"	770	FI
215/70R16 104T XL Double Action Stud Technology	None	1,984 lbs	51 psi	11.5/32"	28 lbs	5.5-7"	6.5"	8.7"	6.9"	27.9"	747	FI
225/55R16 99T XL Double Action Stud Technology	None	1,710 lbs	51 psi	11.5/32"	25 lbs	6-8"	7"	9.2"		25.8"	807	FI
245/70R16 111T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	35 lbs	6.5-8"	7"	9.8"		29.5"	706	FI
265/70R16 116T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	40 lbs	7-9"	8"	10.7"		30.6"	681	FI



Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
205/50R17 93T XL Double Action Stud Technology	None	1,435 lbs	51 psi	11.5/32"	22 lbs	5.5-7.5"	6.5"	8.4"		25.1"	826	FI
205/55R17 95T XL Double Action Stud Technology	None	1,520 lbs	51 psi	11.5/32"	22 lbs	5.5-7.5"	6.5"	8.4"		25.9"	800	FI
215/50R17 95T XL Double Action Stud Technology	None	1,520 lbs	51 psi	11.5/32"	25 lbs	6-7.5"	7"	8.9"		25.5"	813	FI
215/55R17 98T XL Double Action Stud Technology	None	1,655 lbs	51 psi	11.5/32"	25 lbs	6-7.5"	7"	8.9"		26.3"	788	FI
215/60R17 100T XL Double Action Stud Technology	None	1,765 lbs	51 psi	11.5/32"	24 lbs	6-7.5"	6.5"	8.7"		27.2"	764	FI
215/65R17 103T XL Double Action Stud Technology	None	1,929 lbs	51 psi	11.5/32"	29 lbs	6-7.5"	6.5"	8.7"	6.9"	28"	742	FI
225/45R17 94T XL Double Action Stud Technology	None	1,477 lbs	51 psi	11.5/32"	23 lbs	7-8.5"	7.5"	8.9"		25"	834	FI
225/50R17 98T XL Double Action Stud Technology	None	1,653 lbs	51 psi	11.5/32"	26 lbs	6-8"	7"	9.2"	7.3"	25.9"	800	FI
225/55R17 101T XL Double Action Stud Technology	None	1,820 lbs	51 psi	11.5/32"	26 lbs	6-8"	7"	9.2"		26.8"	776	FI
225/60R17 103T XL Double Action Stud Technology	None	1,930 lbs	51 psi	11.5/32"	29 lbs	6-8"	6.5"	9"	7.3"	27.6"	752	FI
225/65R17 106T XL Double Action Stud Technology	None	2,095 lbs	51 psi	11.5/32"	30 lbs	6-8"	6.5"	9"	6.9"	28.5"	731	FI
235/45R17 97T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	24 lbs	7.5-9"	8"	9.3"		25.4"	820	FI
235/55R17 103T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	27 lbs	6.5-8.5"	7.5"	9.6"		27.2"	764	FI
235/60R17 106T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	28 lbs	6.5-8.5"	7"	9.4"		28.1"	742	FI
245/45R17 99T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	27 lbs	7.5-9"	8"	9.6"		25.7"	807	FI
245/65R17 111T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	34 lbs	7-8.5"	7"	9.8"		29.5"	706	FI
255/65R17 114T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	37 lbs	7-9"	7.5"	10.2"		30.1"	691	FI



Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
265/65R17 116T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	39 lbs	7.5-9.5"	8"	10.7"		30.5"	681	FI
265/70R17 116T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	45 lbs	7-9"	8"	10.7"		31.6"	659	FI
215/55R18 99T XL Double Action Stud Technology	None	1,710 lbs	51 psi	11.5/32"	25 lbs	6-7.5"	7"	8.9"		27.3"	764	FI
225/40R18 92T XL Double Action Stud Technology	None	1,390 lbs	51 psi	11.5/32"	22 lbs	7.5-9"	8"	9.1"		25.1"	826	FI
225/45R18 95T XL Double Action Stud Technology	None	1,520 lbs	51 psi	11.5/32"	25 lbs	7-8.5"	7.5"	8.9"		25.9"	800	FI
225/50R18 99T XL Double Action Stud Technology	None	1,710 lbs	51 psi	11.5/32"	25 lbs	6-8"	7"	9.2"		26.9"	776	FI
225/55R18 102T XL Double Action Stud Technology	None	1,875 lbs	51 psi	11.5/32"	26 lbs	6-8"	7"	9.2"		27.8"	747	FI
225/60R18 104T XL Double Action Stud Technology	None	1,985 lbs	51 psi	11.5/32"	30 lbs	6-8"	6.5"	9"	6.8"	28.6"	726	FI
235/40R18 95T XL Double Action Stud Technology	None	1,520 lbs	51 psi	11.5/32"	24 lbs	8-9.5"	8.5"	9.5"		25.4"	820	FI
235/45R18 98T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	25 lbs	7.5-9"	8"	9.3"		26.3"	788	FI
235/50R18 101T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	27 lbs	6.5-8.5"	7.5"	9.6"		27.3"	764	FI
235/55R18 104T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	28 lbs	6.5-8.5"	7.5"	9.6"		28.1"	742	FI
235/60R18 107T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	30 lbs	6.5-8.5"	7"	9.4"		29.1"	715	FI
245/40R18 97T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	27 lbs	8-9.5"	8.5"	9.8"		25.7"	807	FI
245/45R18 100T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	26 lbs	7.5-9"	8"	9.6"		26.6"	781	FI
245/60R18 109T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	32 lbs	7-8.5"	7"	9.8"		29.6"	700	FI
255/40R18 99T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	26 lbs	8.5-10"	9"	10.2"		26"	800	FI



Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
255/55R18 109T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	35 lbs	7-9"	8"	10.4"		29"	715	FI
255/60R18 112T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	35 lbs	7-9"	7.5"	10.2"		30"	691	FI
265/60R18 114T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	38 lbs	7-9.5"	8"	10.7"		30.5"	681	FI
275/65R18 116T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	47 lbs	7.5-9.5"	8"	11"		32.1"	647	FI
225/55R19 103T XL Double Action Stud Technology	None	1,930 lbs	51 psi	11.5/32"	28 lbs	6-8"	7"	9.2"		28.8"	720	FI
235/40R19 96T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	26 lbs	8-9.5"	8.5"	9.5"		26.4"	788	FI
235/50R19 103T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	29 lbs	6.5-8.5"	7.5"	9.6"		28.3"	736	FI
235/55R19 105T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	30 lbs	6.5-8.5"	7.5"	9.6"		29.2"	710	FI
245/40R19 98T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	27 lbs	8-9.5"	8.5"	9.8"		26.7"	781	FI
245/45R19 102T XL Double Action Stud SilentDrive	None	1,874 lbs	51 psi		31 lbs				8.2"			FI
245/50R19 105T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	31 lbs	7-8.5"	7.5"	10"		28.7"	726	FI
255/40R19 100T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	28 lbs	8.5-10"	9"	10.2"		27"	770	FI
255/45R19 104T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	29 lbs	8-9.5"	8.5"	10"		28.1"	742	FI
255/50R19 106T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	35 lbs	7-9"	7.5"	10.4"		29.1"	715	FI
255/55R19 111T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	34 lbs	7-9"	8"	10.4"		30"	691	FI
255/55R19 111T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	35 lbs	7-9"	8"	10.4"		30"	691	FI
275/40R19 105T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	35 lbs	9-11"	9.5"	10.9"		27.7"	752	FI



Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
235/45R20 100T XL Double Action Stud SilentDrive	None	1,764 lbs	51 psi	11.5/32"	30 lbs	7.5-9"	8"	9.3"	7.6"	28.4"	731	FI
235/50R20 104T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	31 lbs	6.5-8.5"	7.5"	9.7"		29.3"	710	FI
235/55R20 105T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	31 lbs	6.5-8.5"	7.5"	9.6"		30.2"	691	FI
245/40R20 99T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	27 lbs	8-9.5"	8.5"	9.8"		27.7"	752	FI
245/45R20 103T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	29 lbs	7.5-9"	8"	9.6"		28.7"	726	FI
255/40R20 101T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	29 lbs	8.5-10"	9"	10.2"		28"	742	FI
255/45R20 105T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	31 lbs	8-9.5"	8.5"	10"		29.1"	715	FI
255/50R20 109T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	34 lbs	7-9"	8"	10.4"		30.1"	691	FI
255/55R20 110T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	36 lbs	7-9"	8"	10.4"		31"	673	FI
265/45R20 108T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	32 lbs	8.5-10"	9"	10.5"		29.4"	706	FI
265/50R20 111T XL Double Action Stud Technology	None	2,403 lbs	51 psi		37 lbs				8.8"			FI
275/35R20 102T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	30 lbs	9-11"	9.5"	10.9"		27.6"	752	FI
275/45R20 110T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	35 lbs	8.5-10.5"	9"	10.8"		29.8"	695	FI
275/50R20 113T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	39 lbs	7.5-9.5"	8.5"	11.2"		30.9"	673	FI
275/55R20 117T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	45 lbs	7.5-9.5"	8.5"	11.2"		31.9"	651	FI
275/60R20 116T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	45 lbs	7.5-9.5"	8"	11"		33"	630	FI
285/45R20 112T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	36 lbs	9-10.5"	9.5"	11.2"		30.1"	691	FI



Size	UTQG	Max. Load	Max. Inflation Pressure	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs. Per Mile	Country of Origin*
245/45R21 104T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	30 lbs	7.5-9"	8"	9.6"		29.6"	700	FI
255/35R21 98T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	29 lbs	8.5-10"	9"	10.2"		28"	742	FI
265/45R21 108T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	34 lbs	8.5-10"	9"	10.5"		30.4"	686	FI
275/35R21 103T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	30 lbs	9-11"	9.5"	10.9"		28.5"	731	FI
275/40R21 107T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	35 lbs	9-11"	9.5"	10.9"		29.6"	700	FI
275/45R21 110T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	35 lbs	8.5-10.5"	9"	10.7"		30.7"	677	FI
285/40R21 109T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	34 lbs	9.5-11"	10"	11.4"		30"	691	FI
285/45R21 113T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	37 lbs	9-10.5"	9.5"	11.2"		31.1"	668	FI
295/40R21 111T XL Double Action Stud SilentDrive	None	lbs	51 psi	11.5/32"	36 lbs	10-11.5"	10.5"	11.9"		30.3"	686	FI
315/40R21 115T XL Double Action Stud Technology	None	2,680 lbs	51 psi	11.5/32"	38 lbs	10.5-12.5"	11"	12.6"		30.9"	673	FI
275/40R22 107T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	35 lbs	9-11"	9.5"	10.9"		30.7"	677	FI
HL275/50R22 116T HL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	42 lbs	8-9"	8.5"	11.2"		32.9"	630	FI
285/40R22 110T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	36 lbs	9.5-11"	10"	11.4"		31"	673	FI
285/45R22 114T XL Double Action Stud Technology	None	lbs	51 psi	11.5/32"	41 lbs	9-10.5"	9.5"	11.2"		32.1"	647	FI
315/35R22 111T XL Double Action Stud Technology	None	2,405 lbs	51 psi	11.5/32"	39 lbs	10.5-12.5"	11"	12.6"		30.7"	677	FI



NOTES

Specifications shown are as accurate as possible based on the information provided to us by the tire manufacturers. The dimensions reflect average values for tires measured on the specified measuring rim width. Individual tires may vary from data shown.

All tires are subject to continuous development. The tire manufacturers and Tire Rack reserve the right to change product specifications at any time without notice or obligation.

*Although regularly updated, the country of origin for tires may vary from what is shown. Unfortunately, we cannot accommodate requests for tires with a specific country of origin.

For assistance selecting products for your vehicle, please contact our sales specialists at 888-541-1777 or via email